

Cold storage for corpses opening front

CFI 80/4 2TN+2BT



Cold storage for corpses to 4 places including 2TN and 2BT front opening.

Technical data

Dimensions lcm180xpcm230xhcm180 + cm40 chiller monoblock, doors lcm70x60, operating temperature of TN -3 °/+ 4 ° BT - 0 °/-20 °, panels SP/cm7 polyurethane high pressure ISO3582 without FC, thermal conductivity 0,015Kcal / mh ° C .

Group power

Power supply 230/1 / 60Hz, TN power 1000W operating temperature -3 $^{\circ}$ / + 4 $^{\circ}$, BT power 1500W temperature -20 / 0 $^{\circ}$, electronic display cell functions and management parameters.

Basic configuration

Coating internal/external sheet of stainless steel AISI 304, adjustable feet, steel rollers to support stretchers, stretchers n4 lcm200xpcm60 steel edging, n4 doors with lock.

Accessories

Coating internal/external sheet zincoplast white, drain water wash, locks with keys, badges steel supports for coffins, n2 single doors.

Complies with CE standards

COMFIT srl

Via Viberti, 4 10141 Torino TO Tel. +39011720085 Fax. +39011728870 comfit@tiscali.it www.comfit.org

Subject to change without notice the technical characteristics of the products shown. All rights reserved. COMFIT Ltd. 05/2014