

Cold storage for corpses TN / BT CFI 80/3



Technical data

Group power

Basic configuration

Accessories

COMFIT srl
Via Viberti, 4
10141 Torino TO
T. 011 720085 - F.011 728870
comfit@tiscali.it
www.comfit.org

Cold storage for corpses 3 seater with front opening

Dimensions lcm90xpcm230xhcm230 + cm50 chiller mono block , n1 doors lcm70x160, TN compartment temperature operation -0°/ + 4°, BT compartment -20°/ -10°, panels SP / cm7 polyurethane high pressure ISO3582 without FC, thermal conductivity 0.015 kcal / mh ° C.

Power supply 230/1 / 50Hz, TN group power 700 W, 600 W cooling capacity -0° / + 4°, temperature range 0°, BT Group power 1300W cooling capacity 1100 W -20°/ -10°, temperature range -20° , electronic display cell functions and management parameters.

Coating int/est zinc sheet plastic, adjustable feet, steel rollers for supporting stretchers removable, n3 lcm200xpcm60 stretchers steel edging, single door.

Complies with CE standards.

Drain water washing

Locks with keys on the door /doors.
Badges steel.
Coating internal / external sheet steel AISI 304.
Rounded edges and corners inside cell.

Number 3 branches.

Oversized for containment of n2 coffins.

Subject to change without notice the technical characteristics of the products shown. All rights reserved. COMFIT sas, 05/2014

Aria nuova in laboratorio...